

STEP UP TO BAJAJ QUTE. THE SMART TAXI



*Only for IDC BS3



Smart Mileage
36 kmp/l*



Smart Maneuverability
3.5 m turning radius



Smart Protection
Monocoque body



Smart Eco-friendly
40% lower CO₂ emission



TECHNICAL SPECIFICATIONS

DESCRIPTION		WHEELS AND TYRES	
ENGINE	Four stroke, Twin spark-ignition, Single cylinder engine, liquid cooled	Front	2.1 kg/cm ² (30psi)
Capacity	216.6 cm ³	Rear	Unladen -2.1 kg/cm ² (30psi), Laden-2.4 kg/cm ² (34psi)
Max. Engine Output	9.9 Kw at 5500	Spare	2.4 kg/cm ² (34psi)
Max. Torque	19.6 Nm at 4000		
CLUTCH	Wet Multi-Disc Clutch	BODY	Steel monocoque body made in high strength steel
TRANSMISSION	Constant Mesh Manual, 5 forward & 1 reverse	WEIGHTS (KG)	
FUEL TANK	8 liters (nominal) Petrol	Unladen Mass	449 Kgs
PERFORMANCE		Gross vehicle weight	749 Kgs
Max. speed	70 km/h, 5th Gear	Payload	300 Kgs
Max. Gradability	20% (11.30 degree) in first gear	SEATING CAPACITY	4, including driver
SUSPENSION		ELECTRICAL SYSTEMS	
Front	Independent Suspension with Twin leading arm, coil over shock absorber & anti roll bar	Battery	12V, 26AH
Rear	Independent suspension with Semi trailing arm and coil over shock absorber	Engine management	ECU, Fuel injected
STEERING	Manual (Rack & Pinion)	Head lamp	60 X 55W HS1
BRAKES	Hydraulic with H-split. All Drum, Dia 180 mm.	Tail/Stop lamp	5/21W
Parking Brakes	Right Foot operated control Mechanical (cable operated) Hand operated, Rear wheel	MAIN CHASSIS DIMENSIONS (IN MM)	
		Overall height (Unladen)	1652
		Overall length	2752
		Wheel Base	1925
		Rear overhang	440
		Overall width	1312
		Wheel track	1143
		Lowest Hard Point From Ground	180 mm – Unladen
		Turning circle radius	3.5 meters
		** Specifications mentioned above are subject to change.	